



Grade1 Sputtering Target Materials Pure Titanium Material 4.51g/cm³ Density

Basic Information

Place of Origin: ChinaBrand Name: N/M

Certification: ISO9001:2015 certification
 Model Number: CDX-TB-2021-010

Minimum Order Quantity: 5 kg
Price: Negotiable
Packaging Details: plywood case
Delivery Time: 5-35 working days
Supply Ability: 50000KG/month



Product Specification

Key Words: Titanium Target Sputtering Coating Titanium

Name: Target Sputtering Coating Titanium
 Application: LCD Screen, Laser Memory, Coating

• Technique: Forged, CNC Machining, Hot Rolled, Forged

And CNC Machined

• Grade: Gr1

• Density: 4.51g/cm3

Key Words 2: Pure Titanium Target

• Highlight: Grade1 Titanium Sputtering Target Materials,

4.51g/Cm³ Sputtering Target Materials, Pure Titanium Sputtering Target



More Images



Product Description

Titanium Target Sputtering Coating Titanium Grade1 Pure Titanium Target

Titanium target

High-purity and high-density sputtering targets include:

Sputtering target (purity: 99.9%-99.999%)

Titanium target plate

High-purity and high-density titanium sputtering target

Titanium target Titanium sputtering target material Used for liquid crystal display, laser memory, electronic controller, sputtering thin film material, semiconductor integrated circuit, solar photovoltaic, recording medium, flat display and surface coating of workpiece

Titanium target Titanium sputtering target material Used for liquid crystal display, laser memory, electronic controller, sputtering thin film material

Titanium target Titanium sputtering target is used for semiconductor integrated circuit,

solar photovoltaic, recording medium, flat display and workpiece surface coating

Titanium target titanium sputtering target is used for semiconductor integrated circuit, solar photovoltaic, recording medium, plane display and workpiece surface coating

Titanium target sputtering coating titanium grade1 pure titanium target

Titanium target with hole titanium target plate perforated

Material:	Pure titanium Gr. 1
	Titanium target Titanium sputtering target material
	Used for liquid crystal display, electronic controller,
	sputtering thin film material,
Application:	semiconductor integrated circuit,
	solar photovoltaic,
	recording medium,
	flat display and surface coating of workpiece
Purity:	99.96% - 99.99%
Custom made:	support
Tolerance:	+/-0.05mm
Shape:	round target, rectangular target

Usually we will provide a quality inspection report like this with the goods, which shows the chemical composition and physical properties

Terms of trade	EXW FOB CIF
Payment terms	T/T , L/C
packing	Plastic paper inside , plywood case outside
Delivery time	In general,the delivery time is 5 days to 35 days. Please confirm the exact delivery time with us as different products and different quantity need different delivery time.
MOQ	Small order quantity is acceptable





Q: Why choose us?

A1: We have 14 years experience for titanium products making.

A2: sample order is acceptable.

A3: lower price, good quality and short delivery time.

A4:The quotation can be make within 24 hours.

A5: ISO9001:2015 certification

A6: Give us drawing, make your drawings and ideas become a reality!

A7: Provide third-party quality inspection reports.

Sputtering targets are mainly used in the electronics and information industries, such as integrated circuits, information storage, liquid crystal displays, laser storage, electronic control devices, etc.; it can also be used in the field of glass coating; it can also be used in wear-resistant materials, high temperature and corrosion resistance, High-end decorative products and other industries.





+8613911115555



test@test.com



titanium-part.com