

# ASTM B265 Gr5 6al4v Pure Titanium Alloy Plate 1mm Thickness

### **Basic Information**

Place of Origin: ChinaBrand Name: CDX

Certification: ISO9001:2015 certification

Model Number: CDX-TB-2022-19

Minimum Order Quantity: 100kg
Price: Negotiable
Packaging Details: plywood case
Delivery Time: 5-35days
Payment Terms: L/C, T/T

Supply Ability: 50000 kg per month



### **Product Specification**

Product Name: Gr1 Gr2 Gr5 Gr7 Gr1 Titanium Grade 4 Coil

Strip Plates

• Standard: ASTM 265, ASTM F136, AMS 4928, ASTM

F67,Hot Sale Gr1 Titanium Bar

Name: Pure Titanium And Titanium Alloy 12mm

Titanium Round Rod,Gr5 6AL4V Titanium Bar Alloy,india Nickel Titanium Shape Memory Alloy 3mm Nitinol Rod,Titanium

Sheet For Skull Mesh

Advantage: Chinese Titanium Valley"-Baoji,High


Performance

Sample: Hot Sale Gr1 Titanium Bar, Available

• Custom Sample: 5-7 Days

• Highlight: 1mm Pure Titanium Sheet,

Titanium Alloy Plate Gr5, Industrial 6al4v Titanium Sheet



## Gr1 Gr2 Gr5 Gr7 Gr1 Titanium Grade 4 Coil Strip Plates Titanium plate

Medical titanium plate
Rolled titanium plate
Hot rolled titanium plate cold rolled titanium plate
Titanium industry plate

Grade 1 titanium plate: Pure Titanium, relatively low strength and high ductility.

Grade 2 titanium plate: The pure titanium most used. The best combination of strength, weldability.

Grade 3 titanium plate : High strength Titanium, used for Matrix-plates in shell and tube heat exchangers.


Grade 5 titanium plate: The most manufactured titanium alloy. Exceedingly high strength. high heat resistance.


Grade 7 titanium plate : Superior corrosion resistance in reducing and oxidizing environments.

Grade 9 titanium plate : Very high strength and corrosion resistance.

Grade 12 titanium plate : Better heat resistance than pure Titanium. Applications as for Grade 7 and Grade 11.

Grade 23 titanium plate: Titanium-6Aluminum- 4Vanadium ELI. Alloy for surgical implant application.





Mill Test Certificate sample 宝丞 金属材料有限公司 Baoji Quality Metals Co., Ltd

量 明 Quality Certificate

号(Certificate

No.):CDX20220625LA								
合同号 Contract No.	品名称 Descriptio n	牌号 Designatio No.	批 号Lot No/ 号 Heat No.	状 Condition	格 Size(m m)	数量 Quantity	品 准 Product Standard	
/	板	TA2	CDX202 14#		20mm× 1000m m×2000 mm	sample	GB/T36	621
室温力学性能	温度( ) Test Temperatu re	抗拉 度 Rm(MPa) Tensile Strength	屈服 度 Rp <sub>0.2</sub> (M Pa) Yield Strengt h	(%) El on gation	断面收 率 Z(%) Reductio n of arca	C	□ Expan ding text	扁 Flattening text
ı	Result	455	330	3 0	/	合格	合格	合格

其它 Others	弯曲 r <sup>o</sup> Bend Test	l		高倍 Microsi ructure	n al In s p ci ic		表面 量 Visual nspecti on		探 Ultrasc Inspec	-	/
//. ** -* - O	<u> </u>	<u>/</u>		/	台格		<b>各</b>	c	k		/
化学成 Chen	nical Comp	osition	()								Daaidual
	Ti	AI	Sn	//	//	ь е			Н		Residual element
Result	Remainder	/	/	//	//	9	0.014	0 0 6	0.0011	0.094	≤ 0 . ≤0.30 1
Prepared by: ≦	Prepared by: <u>李海魁</u> 批准: Report Date: <u>2022年11月8日</u>										
neport bate: 2022411Hot											

package

## **Product Packaging**









Titanium plate Features
Low Density and High Specification Strength
Excellent Corrosion Resistance
Good resistance to effect of heat Excellent Bearing to cryogenic property Nonmagnetic and Non-toxic Good thermal properties Low Modulus of Elasticity

Terms of payment	T/T, L/C
Certification	ISO9001:2015 certification

Delivery time	7-35days
Size	customs made
Density	4.51g/cm3
Packing	Plywood case tied by steel band or as per client requirements
Quality contral	Ultrasonic testing & material test report & VISUAL INSPECTION

## Q: Why choose us?

A1: We have 14 years experience for titanium products making.

A2: sample order is acceptable.

A3: lower price, good quality and short delivery time.

A4:The quotation can be make within 24 hours.

A5: ISO9001:2015 certification

A6: Give us drawing, make your drawings and ideas become a reality!

A7: Provide third-party quality inspection reports.





+8613911115555



test@test.com



titanium-part.com

GAOYA INTERSECTION, BAOTAI ROAD GAOXIN DISTRICT, BAOJI SHAANXI CHINA